orig.	arf. nam:	: 12 figures	•		ntral tube for	the low-p	ressure gas. [PV]
SUB CO	DE: 21/	SUBM DATE:	06Apr66/	ATD PRESS:	5063		•
	All a Carren	•			•		
		•				i.	
			•		•	•	
	•		,				
	•						400 M
			•				***
-				•			

ACC NR: AT6008853 SOURCE CODE: UR/0000/65/000/00 AUTHOR: Fertik, S. M.; Taller, Ye. G.; Konotop, V. V.; Linetskiy, V. Ya.; ORG: none	Gladkov, v.
S.; Goliushko, G. M.; Hiller, Ye. G.; Konotop, V. V.; Linetskiy, V. Ya.;	Gladkov, v.
ORG: none	1
	ı
TITLE: Design of a capacitor bank with stored energy of 625 kJ for the pro-	oduction or
137-146 AN Ukrssr. Magnitnyye lovushki (Magnetic traps). Kiev, Naukova dum	nka 1065
power source, electric network/ KTMS 1Vacca itance, electric inductance.	electric
rated 625 kJ and intended to operate at four different charging voltages (50 and 250 kv), with much larger operating life than earlier designs (not less stages of the development consisted of designing a special capacitor (type K rated 10 µF (12.5 kJ), and a special system of interconnecting and switching capacitor bank, consisting of special discharge gaps and various high-voltag and safety during discharge are also discussed. Orig. art. has: 4 figures.	acitor bank 0, 100, 200, than The main KIMS-1),
SUEM DATE: 200ct65	
Card 1/1	

CIA-RDP86-00513R000824320015-6 "APPROVED FOR RELEASE: 06/19/2000

ACC NR. ATGOO8854

SOURCE CODE: UR/0000/65/000/000/0147/0156

AUTHOR: Konotop, V. V.; Gladkov, V. S.; Nemchenko, Yu. S.

TITLE: Investigation of the operation of a capacitor bank with stored energy 625 kJ using a physical model

SOURCE: AN UkrSSR. Magnitnyye lovushki (Magnetic traps). Kiev, Naukova dumka, 1965,

TOPIC TAGS: electric network, test model, electric capacitor, differential equation ABSTRACT: The authors describe a model constructed to simulate the low-inductance capacitor bank described in a companion paper (Acc. Nr. AT6008853). The equivalent circuit of the battery consisted of 99 reactive elements, so connected that the order of differential equations to be solved is reduced to 29. The purpose of the test was to check whether the capacitor bank is correctly connected (the switching elements installed in the proper places), to determine the voltages that can occur in the capacitor-bank elements during normal and emergency conditions, and to assess the effect of different lengths of the interconnecting cables on the operation of the bank. Low-voltage capacitors (KBG, KSO, and KTK) were used in the model. The coaxial cable was replaced by artificial lines with lumped constants. Tables showing the characteristics of the different circuits and oscillograms showing the results of simulated transient tests are presented. The emergency conditions simulated wre a short circuit

Card 1/2

ACC NR: AT6008854


of the load, a short circuit of the cable during the charging of the capacitor bank, and a short circuit of one capacitor at nominal charging voltage. The tests have shown that the increase in the current of individual capacitors occurring under the abnormal conditions does not exceed the safety factor incorporated in the design. Orig. art. has: 5 figures, 5 formulas, and 2 tables.

SUB CODE: 09/ SUBM DATE: 200ct65

Card 2/2

AUTHOR: Konotop, V. V.; Linetskiy, V. Ya.; Fertik, S. M. ORG: Khar'kov Polytechnic Institute (Khar'kovskiy politekhnicheskiy institut) TITLE: High-voltage low-inductance capacitors with a built-in trigatron SOURCE: Pribory i tekhnika eksperimenta, no. 6, 1965, 121-123 TOPIC TAGS: capacitor, high voltage capacitor, electric inductance/ KIM capacitor ABSTRACT: As most of the undesirable inductance of a h-v impulse generator lies in the conductors comecting the storage capacitor with its trigatron discharger, a combined trigatron-capacitor design is proposed (see similar ideas in Sc. Instr., 1961, 38, no. 4, 136, by A. H. Gabriel et al.). The inductance of a conventional 20-kv trigatron-capacitor circuit used to be 40 nH; the combined design of the same elements showed an inductance of only 15 nH. Some new combined capacitors developed current impulses over 600 ka. In some cases, a load (e.g., a discharge tube), instead of the trigatron, was built into the capacitor structure. Orig. art. has: 5 figures, 2 formulas, and 1 table. SUB CODE: 09 / SUBM DATE: 05Oct64 / ORIG REF: 003 / OTH REF: 001		L 22691-66 EMT(1)/WA(N) ACC NR. AP6001577 (A) SOURCE CODE: UR/0120/65/000/006/0121/0123			
ORG: Khar'kov Polytechnic Institute (Khar'kovskiy politekhnicheskiy institut) TITLE: High-voltage low-inductance capacitors with a built-in trigatron SOURCE: Pribory i tekhnika eksperimenta, no. 6, 1965, 121-123 TOPIC TAGS: capacitor, high voltage capacitor, electric inductance/ KIM capacitor ABSTRACT: As most of the undesirable inductance of a h-v impulse generator lies in the conductors comecting the storage capacitor with its trigatron discharger, a combined trigatron-capacitor design is proposed (see similar ideas in Sc. Instr., 1961, 38, no. 4, 136, by A. H. Gabriel et al.). The inductance of a conventional 20-kv trigatron-capacitor circuit used to be 40 nH; the combined design of the same elements showed an inductance of only 15 nH. Some new combined capacitors developed current impulses over 600 ka. In some cases, a load (e.g., a discharge tube), instead of the trigatron, was built into the capacitor structure. Orig. art. has: 5 figures, 2 formulas, and 1 table.		AUTHOR: Konotop, V. V.; Linetskiy, V. Ya.; Fertik, S. M.		Į	
TITLE: High-voltage low-inductance capacitors with a built-in trigatron SOURCE: Pribory i tekhnika eksperimenta, no. 6, 1965, 121-123 TOPIC TAGS: capacitor, high voltage capacitor, electric inductance/ KIM capacitor ABSTRACT: As most of the undesirable inductance of a h-v impulse generator lies in the conductors comecting the storage capacitor with its trigatron discharger, a combined trigatron-capacitor design is proposed (see similar ideas in Sc. Instr., 1961, 38, no. 4, 136, by A. H. Gabriel et al.). The inductance of a conventional 20-kv trigatron-capacitor circuit used to be 40 nH; the combined design of the same elements showed an inductance of only 15 nH. Some new combined capacitors developed current impulses over 600 ka. In some cases, a load (e.g., a discharge tube), instead of the trigatron, was built into the capacitor structure. Orig. art. has: 5 figures, 2 formulas, and 1 table.	1	ORG: Khar'kov Polytechnic Institute (Khar'kovskiy politekhnicheskiy institut)		I	
SOURCE: Pribory i tekhnika eksperimenta, no. 6, 1965, 121-123 TOPIC TAGS: capacitor, high voltage capacitor, electric inductance/ KIM capacitor ABSTRACT: As most of the undesirable inductance of a h-v impulse generator lies in the conductors comecting the storage capacitor with its trigatron discharger, a combined trigatron-capacitor design is proposed (see similar ideas in Sc. Instr., 1961, 38, no. 4, 136, by A. H. Gabriel et al.). The inductance of a conventional 20-kv trigatron-capacitor circuit used to be 40 nH; the combined design of the same elements showed an inductance of only 15 nH. Some new combined capacitors developed current impulses over 600 ka. In some cases, a load (e.g., a discharge tube), instead of the trigatron, was built into the capacitor structure. Orig. art. has: 5 figures, 2 formulas, and 1 table.					
ABSTRACT: As most of the undesirable inductance of a h-v impulse generator lies in the conductors comecting the storage capacitor with its trigatron discharger, a combined trigatron-capacitor design is proposed (see similar ideas in Sc. Instr., 1961, 38, no. 4, 136, by A. H. Gabriel et al.). The inductance of a conventional 20-kv trigatron-capacitor circuit used to be 40 nH; the combined design of the same elements showed an inductance of only 15 nH. Some new combined capacitors developed current impulses over 600 ka. In some cases, a load (e.g., a discharge tube), instead of the trigatron, was built into the capacitor structure. Orig. art. has: 5 figures, 2 formulas, and 1 table.				ı	
ABSTRACT: As most of the undesirable inductance of a h-v impulse generator lies in the conductors comecting the storage capacitor with its trigatron discharger, a combined trigatron-capacitor design is proposed (see similar ideas in Sc. Instr., 1961, 38, no. 4, 136, by A. H. Gabriel et al.). The inductance of a conventional 20-kv trigatron-capacitor circuit used to be 40 nH; the combined design of the same elements showed an inductance of only 15 nH. Some new combined capacitors developed current impulses over 600 ka. In some cases, a load (e.g., a discharge tube), instead of the trigatron, was built into the capacitor structure. Orig. art. has: 5 figures, 2 formulas, and 1 table.					
SUB CODE: 09 / SUBM DATE: 05Oct64 / ORIG REF: 003 / OTH REF: 001		in the conductors comecting the storage capacitor with its trigatron discharger, a combined trigatron-capacitor design is proposed (see similar ideas in Sc. Instr., 1961, 38, no. 4, 136, by A. H. Gabriel et al.). The inductance of a conventional 20-kv trigatron-capacitor circuit used to be 40 nH; the combined design of the same elements showed an inductance of only 15 nH. Some new combined capacitors developed current impulses over 600 ka. In some cases, a load (e.g., a discharge tube), instead of the trigatron, was built into the capacitor structure. Orig. art. has: 5 figures, 2 formulas, and 1 table.			
		SUB CODE: 09 / SUBM DATE: 05Oct64 / ORIG REF: 003 / OTH REF: 001		-	
Card 1/1 // W UDC: 537.54		Card 1/1 # WDC: 537.54	2		

	10.15.15 10.15.15.
	-
44	0
Apple Apple	
	1.00
graphy, reight intigration as follows in the con-	7.7
poignist	
Some bestive so estyl i modifik it - a poling, som it based it properties and	0
State, besking so (SIV) a morning for the large state of the large sta	
in the formulation of the second	
to the processors are conducted in the copy of the first one radiation grafting	
or 0, 5 without the profile.	
or the grant of the parythern in the following the second of the flat conclumers were	
component arm spectra were taken with the control of the control o	
	2
Cord $1/2$	
(1)	



Konov, AAPPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320015-6" farmers of the grain collective farm Kurash ", Khlebinkov rayon of Mariyak ASSR), Surmary. Moledost', Book 7, 1940, p. 49-55.

SO: U-3850, 16 June 53, (Letonis 'Zhurnal 'nykh Statey, No. 5, 1949).

THE RESIDENCE OF THE PROPERTY OF THE PARTY O

KONOV, I.I.; MAKAROV, L.M.

New method for the alignment of the disk spindle axle on internal grinding machines. Podshipnik no.7:31-32 J1 153. (MLM 6:8)

(Grinding and polishing)

AUTHORS: Konov, K. I. and Anders, N. R. 94-13-7-8/25

TITLE: An Improved Electric Furnace for High Temperature

Reduction of Tungsten by Hydrogen (Usovershenstvovannaya elektropech' dlya vysokotemperaturnogo vosstanovleniya

vol'frama vodorodom)

PERIODICAL: Promyshlennaya Energetika, 1958, Vol 13, Nr 7, pp 16-17 (USSR)

ABSTRACT: This suggestion was awarded a fifth premium in an All-Union Power economy competition. Hitherto tungsten was reduced by hydrogen in imported continuous electric muffle furnaces of 33 kW rating operating at 220 V and illustrated in Fig.1. The imput was regulated by hard

illustrated in Fig.1. The imput was regulated by hand by means of rheostats. The authors developed and introduced a new continuous high-output furnace illustrated in Fig.2. The furnace was made longer, two tungsten heating muffles were connected in series and shields were constructed to reduce heat losses. The


furnace is supplied by three auto-transformers of 380/50 V each of 6 kVA output. Technical data relating to the

Card 1/2

An Improved Electric Furnace for High Temperature Reduction of Tungsten by Hydrogen

old and new furnaces are compared in a table. There are 2 figures and 1 table.

Card 2/2 1. Electric furnaces - Design 2. Tungsten - Reduction 3. Hydrogen - Applications



KONOV, M. N.

Tractors


Year's operation of tractors KT-12 equipped with gas generators TSNIIME - 17., Les. prom., 12, no. 1, 1952.


9. Monthly List of Russian Accessions, Library of Congress, Parch, 1952 1993, Uncl.


ECHOV, H. Technical documentary of the electric products industry. p.3.

LECTROMERCIIA. Sofiya. Vol. 6, no. 5, Nay 1955.

SO: Monthly List of the East European Accessions. (EEAL), LC. Vol. 4, no. 10, Oct. 1955. Uncl.







KONOV, V., inzh.; SAKHAROV, S., inzh.; SUBBOTIN, I., inzh.; CHEREMNYKH, Y., inzh.;

KARYAKO. B., inzh.; RASSHCHEPKIN, V., inzh.; BORISOVA, T., inzh.;

PROPERTY D. Inzh.; GARMASH, V., inzh.; GOLOVINA, V., inzh.;

New developments in building practice. Na stroi. Ros. 4 no.1:7,11,14,18,

(MIRA 16:3)

(Building—Technological innovations)

THE RESERVE THE PROPERTY OF TH

Replacing the casing of a milling machine. Thement 17 no.6:
22 E-D '56. (MIRA 9:8)

1. Sengeleyevskiy tementryy savod.
(Crushing machinery...Maintenance and repair)

90

The Effect of Nuclear Radiation (Cont.)

SOV/6176

PURPOSE: This book is intended for personnel concerned with nuclear materials.

COVERAGE: This is a collection of papers presented at the Moscow Conference on the Effect of Nuclear Radiation on Materials, held December 6-10, 1960. The material reflects certain trends in the work being conducted in the Soviet scientific research organization. Some of the papers are devoted to the experimental study of the effect of neutron irradiation on reactor materials (steel, ferrous alloys, molybdenum, avial, graphite, and nichromes). Others deal with the theory of neutron irradiation effects (physicochemical transformations, relaxation of internal stresses, internal friction) and changes in the structure and properties of various crystals. Special attention is given to the effect of intense Y-radiation on the electrical, magnetic, and optical properties of metals, dielectrics, and semiconductors.

Card 2/14

The Effect of Nuclear Radiation (Cont.)	ov/6176
Astrakhontsev, S. M., and Yu. I. Komnov. Effect of Neutron Irradiation on Inhomogeneous Salid Solutions Specimens of X20H80 [N180Cr20] alloy were irradiated at a temperature not exceeding 100° [C?] by a thermal neutron of 1.1017 to 1.4.1020 n/cm2.	121 flux
Sayenko, G. P. Effect of Neutron Irradiation on Ordering Fe _s Alloy Specimens were irradiated by fast neutrons and measurements were made of electric resistance, lattice parameter and the intensity of superlattice lines.	127
Ivanov, A. N., and N. F. Pravdyuk. Effect of Neutron Irradition on Electrical Resistance in Certain Metals	.a- 136
Pravdyuk, N. F., and P. A. Plastonov. Study of Long-Time Strength of Copper After Irradiation The investigation was conducted before and after irradia- tion with a neutron flux of =10° n/cm².	153
Card 7/14	
	a de la companya de l

S/137/60/000/009/019/029 A006/A001

The Effect of Rare-Earth Elements on the Structure of Fracture and the Structure

at a teeming temperature of 1,550°C the addition of 0.3% misch metal to the steel prevents the formation of intergranular fractures of cast steel. There are 7

T.F.

Translator's note: This is the full translation of the original Russian abstract.

Card 2/2

KONOV, Yu. K., ZINOVYEVA, T. N., KOLODNAYA, B. A. (Engineers), and FRIDLYAND, I. A. (Cand. Tech. Sci.) (Moscow)

"Investigation of processes of joining titanium-aluminum and aluminum--steel" was devoted to a study of the behavior during dynamic loading of constructions, achieved by welding and by rolling and welding by explosion. A technology was developed which involved preliminary hard-facing on titanium of technically pure aluminum AVOO or AVOOO either with calorizing or without it. Thickness of the layer of hard-facing is 5--8 mm. Welding is carried out by arc in argon by melted or unmelted electrode. Ultimate strength of joining OT4 with AMg6-11 is 24 kG/mm², angle of bend 17./30°.

Report presented at the 1st All-Union Conference on welding of heterogeneous metals, at the Inst of Electric Welding im. Ye. O. Paton, 14-15 June 1963. (Reported in Avtomaticheskaya svarka, Kiev, No. 9, Sept 1963, pp 95-96 author V. R. Ryabov)

JPRS 24,651

19 May 64

	L 34668-66 T/EWP(t)/ETI IJP(c) JD ACC NR:AF6014717 SOURCE CODE: BU/0011/66/019/001/0013/0016 AUTHOR: Nadzhakov, G.; Konova, A.; Pakeva, S. ORG: Sofia University, Physics Department (Fizicheskiy fakul'tet, Sofiyskiy Universitet) TITLE: Photoelectret effect in small cadmium sulfide single crystals SOURCE: Bulgarska akademiya na naukite. Doklady, v. 19, no. 1, 1966, 13-16 TOPIC TAGS: photoelectret, semiconductor research, semiconductor single crystal, cadmium sulfide, dielectric property, single crystals dispersed in araldite resin were attuited to determine whether a photoelectret effect can be produced in small single crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as in large ones. The measurement results show that 1) one part CdS to crystals as three parts resin is the most effective ratio, 2) the permanent polarization varies three parts resin is the depending on the ratio of CdS to resin, 3) photo-		
•	three parts resin is depending on the ratio of CdS to resin, from sample to sample depending on the ratio of CdS to resin, from sample to sample depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization time regardless of illumination polarization saturation depends on polarization depends on polarization saturation depends on polarization depends		
	Card 1/2		

elecret ellec	materials em igures and l	haterocharge and the photopolarisation values do not arity. The results lead to the concellision that the photoduced in small single crystals as in large single crystaployed must have a high dark specific resistance. Originally table.					Orig.			
SUB CODE: 20/	SUBM DATE:	21Sep65/	ORIG REF	001/ SOV	REF: 007,					
		• •	* , •				8			
•										
•••			•		•		•			
:		-		•						
		•								

"APPROVED FOR RELEASE: 06/19/2000

CIA-RDP86-00513R000824320015-6


IJP(c) T/EWP(t)/ETI BU/0011/65/018/012/1087/1090 L 36027-66 SOURCE CODE: ACC NR. AP6027347 AUTHOR: Nadzhakov, G.; Antonov, A.; Pakova, S.; Konova, A. ORG: none TITIE: Conservation of the homocharge during the dark polarization of sulfur 27 monocrystals 4 SOURCE: Bulgarska akademiya na naukite. Doklady. v. 18, no. 12, 1965, 1087-1090 TOPIC TAGS: dielectric polarization, photoelectret, electric field, single crystal ABSTRACT: The creation of photoelectret states within dielectrics is accompanied by dark polarization, i.c., polarization in darkness by means of applied electric fields. During such polarization the surface may acquire hetero- as well as homocharges. G. Nadzhakov et al. (Dokl. BAN, 15, 1962, no. 8, 805) assumed carlier that the applied high voltage causes the ions within the dielectric to be absorbed. The present investigation studied, consequently, in more detail, the creation and decay (in time) of the homocharge during dark polarization of sulfur monocrystals. Diagrams present the time dependence of the polarization, depolarization, and homocharge decay with the applied voltage (1-5 kV) as parameter. The paper ends with a brief discussion of the results. Orig. art. has: 4 figures. [JPRS: 36,465] SUB CODE: 09, 20 / SUBM DATE: 21Sep65 / ORIG REF: 003 / SOV REF: 003 OTH REF: 002 Card 1/1 MLP

NADZHAKOV, G.; ANTONOV, A.; ZADAROZHNYY, G. [Zadarozhnii, G.]; KONOVA, A.;
PAKEVA, S.; YUSKESELIYEVA, L. [IUskeselieva, L.].

A new type of two-layer electret. Doklady BAN 17 no.4:365-368 '64.

NACHEV,L.; KONOVA,I.; GESHEVA, R.

Biosynthesis of vitamin B 12 by actinomycetes cultured on solid media. Izv. mikrobiol. inst. (Sofiia) 16:207-212 164



KONOVA, I. V.

"The Metabolism of a Representative Group of Actinomyces Griseus in Relation to Antibiotic Activity." Cand Biol Sci, Inst of Microbiology, Acad Sci USSR, 29 Dec 54. (VM, 21 Dec 54)

Survey of Scientific and Technical Dissertations Defended at USSR Higher Educational Institutions (12) SO: Sum. No. 556 24 Jun 55

IYERUSALIMSKIY, N.D.; KONOVA, I.V.; HERONOVA, N.M.

Determining vitamins and antibiotics by diffusion into agar. Report No. 1: Simplified computations for the dish method. Mikrobiologiia 28 no.3:433-443 My-Je '59. (MIRA 13:3)

1. Institut mikrobiologii AN SSSR.

(YITAMINS, determ.

simplified computations for cup method (Rus))

(ANTIBIOTICS, determ.

same)

KONOVA, I.V.; NERONOVA, N.M.; IYERUSALIMSKIY, N.D.; BORISOVA, A.I.

Determining vitamins and antibiotics by diffusion into agar. Report

Mo.2: Quantitative determination of vitamin B12 and its derivatives
by paper chromatography. Mikrobiologia 28 no.4:490-494 Jl-Ag '59.

(MIRA 12:12)

1. Institut mikrobiologia AN SSSR.

(VITAMIN B12 chem.)

(ESCHERICHIA COLI)

17 (4) AUTHOR:

Konova, I. V.

sov/20-126-3-59/69

TITLE:

Physico-chemical Indices of the Medium (pH, Eh, rH₂) in the Development of Actinomyces Griseus and Its Production of Antibiotic Substance (Fiziko-khimicheskiye pokazateli sredy (pH, Eh, rH₂) pri razvitii Actinomyces griseus i obrazovanii

im antibioticheskogo veshchestva)

PERIODICAL:

Doklady Akademii nauk SSSR, 1959, Vol 126, Nr 3, pp 671 - 674

(USSR)

ABSTRACT:

It is known that the activity of the microorganism species proceeds within a certain rigid physico-chemical framework. The 3 indices mentioned in the title are the most important factors which determine the degree of usefulness of one or the other medium for the development of various microorganisms: active acidity and redox conditions of the medium as they are indicated by symbols in the title. I) Although most actinomycetes (Ref 1) grow between pH 5 - 9, there are, however, species the useful zone of which lies between pH 4.2 and 11. The process of the change of the pH-values is finally caused by specific properties of the metabolism of the bred organism and by the

Card 1/3

Physico-chemical Indices of the Medium (pH, Eh, rH₂) SOV/20-126-3-59/69 in the Development of Actinomyces Griseus and Its Production of Antibiotic Substance

composition of its culture medium. The medium is among other things sometimes acidified, the alkaline pH-initial value is not able to prevent this (Rofs 5,9). The author investigated the change of the active acidity during the development of Actinomyces griseus and during the production of the antibiotic in culture media with 10 different pH-initial values (4.23 - 8.69). The obtained results are given in the figures 1 and 2. They show that pH 4.23 (initial value) does no more belong to the medium acidity favorable for the Actinomycetes. It is obvious that this organism actively regulates the pHvalue of the medium. It secures thus conditions for the processes of metabolism among these also for the production of the antibiotic. II) A certain dependence exists between the amount of the redox potential of the medium and the vital activity of an organism bred with respect to this. Data given on this in the publications are rare (Refs 3,8). From the author's experiments it is concluded that Actinomyces griseus grows in a medium with rH2 19 - 28 under the conditions of the depth

Card 2/3

Physico-chemical Indices of the Medium (pH, Eh, rH₂) SOV/20-126-3-59/69 in the Development of Actinomyces Griseus and Its Production of Antibiotic Substance

culture (glubinnoye vyrashchivaniye). The highest antibiotic activity was detected in the case of a reduced redox potential. There are 3 figures, 1 table, and 9 references, 4 of which are Soviet.

ASSOCIATION: Institut mikrobiologii Akademii nauk SSSR (Institute of Micro-

biology of the Academy of Sciences, USSR)

PRESENTED: February 23, 1959, by V. N. Shaposhnikov, Academician

SUBMITTED: September 6, 1958

Card 3/3

SKRYABIN, G.K.; KOMOVA, I.V.; KOKHLOVA, Yu.M.

International symposium on antibiotics. Mikrobiologica 29 no.1:
154-157 Ja-F '60. (MIRA 13:5)

(APTIBIOTICS--COMGRESSES)

IYERUSALIMIKIY, N.D.; KONOVA, I.V.; NERONOVA, N.M.; ANCHUROVA, A.I.

Determination of vitamin B_{12} by the bicautographic method. Vit. res. i ikh isp. no.5:119-132 '61. (MIRA 15:1)

1. Institut mikrobiologii AN SSSR, Moskva. (CYANOCOBALAMINE) (BIOLOGICAL ASSAY)

KONOVA, ILV.; BORISOVA, A.I.

Production of vitamin B₁₂ by Act. olivaceus on a synthetic medium.
Mikrobiologiia 30 no.1:27-34 Ja-F '61. (MIRA 14:5)

(ACTINOMYGES) (GYANOCOBALAMINE)

KONOVA, I.V.; FATEYEVA, M.V.; IYERUSALIMSKIY, N.D.


First International Symposium in Italy. Mikrobiologiia 30 no.2:
371-374 Mr-Ap '61. (MIRA 14:6)


(FERMENTATION—CONGRESSES)


SHALOSERIKOV, V.H.; KOTCHA, I.V.; LISERIKA, L.I.

Fossible use of meetone-butyl mash for the production of vitation B12 from Act. ollvaceus. Mikrobiologiia 31 no.A:716-719 (MHA 18:3)

1. Institut mikrobiologii AN SSSR.







SHAPOSHNIKOV, V.N. KONOVA, I.V. BORISOVA, A.I.

Vitamin B₁₂ synthesis by Actinomyces olivaceus in a synthetic medium in the presence of 5,6-dimethyl benzimidazole. Mikrobiologiia 32 no.4:598-602 Jl-Ag '63. (MIRA 17:6)

l. Institut mikrobiologii AN SSSR.

LISENKOVA, L.L.; KONOVA, I.V.

Methods of vitamin B₁₂ assay by a diffusion method using Escherichia coli 113-3. Mikrobiologiia 32 no.5:885-890 S-0'63 (MIRA 17:2)

1. Institut mikrobiologii AN SSSR.

KONOVA, I.V.; LISENKOVA, L.L.

Biosynthesis of vitamins of the B₁₂ group by Actinomyces olivaceus on a synthetic medium. Izv. AN SSSR. Ser. biol. no.5:760-761 S-0 '65. (MIRA 18 (MIRA 18:9)

1. Institut mikrobiologii AN SSSR, Moskva.

KONOVA, I.V.; NACHEV, L.; GESHEVA, R.

Production of vitamin B₁₂ by Actinomyces, grown on solid media of various composition. Mikrobiologiia 34 no.3:528-532 My-Je '65. (MIRA 18:11)

1. Institut mikrobiologii AN SSSR.

KONOVA, K. P.

"Concerning Active Immunization Against Measles by a Dry-Virus-Vaccine Produced from a Chick Embryo" Proceedings of Inst. Epidem and Microbiol im. Gamaleya 1954-56.

Other Personnel Identified as Participants in Sessions of the Institute's Scientific Council Held During 1955. Inst. Epidem and Microbiol im. Gamaleya AMS USSR


SO: Sum 1186, 11 Jan 57.

KONOVA, K.P.

Comparative study of the biological activity of staphylococci strains of various origins. Zhur. mikrobiol., epid. i immun. 41 no.9:117-123 S *64. (MIRA 18:4)

1. Institut epidemiologii i mikrobiologii imeni Gamalei AMN SSSR.

Extermination of staphylococcal hemolysins by the technicque of hemolysis neutralization with antistaphylococcal sera on agar plates. Zhur_mikrobiol., epid. i immun. 42 no.2:110-115 F '65, (MIRA 18:6) 1. Institut epidemiologii 1 mikrobiologii imeni Gamalei AMN SSSR.




NIKOLOV, N.; RAICHEV, R.; KONOVA, L.; GEORGIEVA, M.

Two cases of Brenner tumor. Khirurgiia, Sofia 9 no.3: 272-274 1956.

(BRENNER TUMOR, case reports (Bul))

(OVARIES, neoplasms, Brenner tumor, case reports (Bul))



CATEGORY : Cultivated Plants. Fodder Grasses. Root Grops.

ABS. JOUR. : RZhBiol., No. 3. 1959, No. 10985

AUTHOR

: Konova, L.

INST. TITLE : Knezh (Bulgaria) Scientific Research Agricultural Inst. : A Study of the Grass Mixtures of Perennial Grasses with

a Short Period of Utilization.

TG. PUB. : Nauchmi tr. M-vo zemed. i gorite. Ser. rasteniyev"datvo,

1958, 3, No. 1, 23-36

MESTRACT

: A study of the productivity of various grass mixtures when sown on typical chernosem was conducted at the Scientific Research Agricultural Institute in Knezh (Buigaria) during 1952-1956. Sown on the plots were: tall oat-grass and Italian rye-grass (Lolium multiflorum) awnless broms grass and cocksfoot (Dactylis glomerata), red clover, alfalfa end esparcet. In the simple (binary) mixtures, the ratio of the legumes and cereals was 50:50 and in the compound mixtures - 60:40. Botanical analysis of the hay and the identification of the root residues

CARD: 1/2

-73-

mixtures a higher rate of sowing for leguminous grasses than for cereals. - V. S. Shmal'ko

CARD: 2/2

-APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320015

KONOVA, L.; IVANOVA, Khr.; ZOGRAFSKI, P.

Delivery of premature infants with the aid of a speculum, Suvr. med. 13 no.3:24-30 62.

1. Iz Purvi rodilen dom "Tina Kirkova" - Sofiia (Glaven lekar St. Iliev) Nauchno-izsledovatelski institut po akusherstvo i ginekologiia (Direktor dots. Br. Papazov). (INFANT, PREMATURE) (DELIVERY)

GERASIMENKO, G.; kONOVA, T.

Role of credit in the organization of working capital. Den. i kred.
(MIRA 15:1)
(Rostov Province--Machinery industry--Finance)
(Gorkiy Province--Machinery industry--Finance)

KONOVALICHIKOV, G.D.: SMOLENSKAYA, K.S.

Complicated retrobulbar neuritis. Zdrav. Belor. 6 no. 10:62 0 '60. (MIRA 13:10)

1. Iz otolaringologicheskogo i glaznogo otdeleniy oblastnoy bol'nitsy, g. Vileyka.

(OPTIC NERVE--DISEASES)

KONOVALICHIKOV, G.D.

Diagnostic value of determining the C-reactive protein of the blood serum in chronic sinusitis. Zhur. ush., nos. i gor. bol. 24 no.1:73-75 Js.-F '64. (MIRA 18:3)

l. Iz kliniki bolezney ukha, gorla i nosa (dir... zasluzhennyy deyatel' nauki prof. A.G. Likhachev) I Moskovskogo ordena Lenina meditsinskogo instituta imeni Sechenora.

Keneval'chickov, L.D

Cahdensziian of isobatenylmagnesium chloride with carbonyl compounds and tenury useus. A. D. Ferrov. Mendelev Chem. Technol Inst. Moscow. Zhur. Obinchet Khim. 25, 1808-71(1885).—To 3 g. Mg under Et.O there was added a little CHi. CM-CHi.(1), and when the reaction had commenced, a soin of 226.5 g. I and 74 g. AcOMe in 1.5 1. Et.O was added over 10 hrs.; distn. gave 63% tertiary alc., Culluo, bu 90-1°, n. 18 1.4520, da. 0.8538, which hydrogenated over Raney Ni at 130° and 160 atm. to the alc. Culluo, bu 90-7°, n. 18 1.4322, da. 0.8252, which treated with HCl at 70° gave the chloride Culluci, bu 72-3°, n. 19 1.4355, da. 0.8377, which was identified as 4-chloro-2, 46-trinachylheptane. This (35.4 g.) and 27.18 g. I treated with 3 g. Mg yielded as a main product (42%) of an olefin, bu 94-6°, n. 14490, da. 0.8004, which bydrogenated to 2,4,5-trinachyl-4-isobatylheptane, bu 108-9°, n. 14352, da. 0.7812. Treatment of I and pinaceline with Mg (73 g.) run as above, gave 142 g. 2,2,3-tetramethyl-4-keen-5-ch, b. 46°, n. 18 1.4502, da. 0.8514 (oxidation of this gave MesCO and a hydroxy acid, m. 141° (cf. C. A. 49, 108555)) which treated with HCl at 0° gave but 0.5% yield of the corresponding chloride and 80% dichloride, n. 14 1.4710, bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368, da. 0.8303, identified as 3,2,3,5-bu 81.6-4.8°, n. 18 1.4368.

العالم المحارك الأمارية الأوروب المتعدد المعدود الأراب المتعدد والأراب المتعدد والمتعدد والم

the corresponding chloride, by 72.6-3.5°, at 1.4455, da; 0.87-78. This (60.0 g.) and 60.55 g. I with 48.6 g. Mg gave the corresponding chloride, by 72.6-3.5°, at 1.4455, da; 0.87-78. This (60.0 g.) and 60.55 g. I with 48.6 g. Mg gave 36.76 defax, Cullin, by 62.5°, at 1.44 da 0.8161, which hydrogenated to 2.46.4 minthly 4-tentary-authorfelass, by 105.5-6°, at 1.4460, dx 0.7905. Treatment of 36 g. 2.3, 3.5 tetramethyl-3-chloropropane with 13 g. Mg and 36.2 g. I gave 2.8 g. olefin, by 45-7°, at 1.4350, dx 0.7743, which hydrogenated to 2.3, 3, 5-pentamethylherane, bis 172-3°, at 1.260 dx 0.7621. 2.2, 3, 5-tetramethyl-3-chloroberane, 61.22 g. CH; CHCHcCl and 24 g. Mg gave an olefin (27.2 g.) b; 66-8°, at 1.4521, dx 0.5034, which hydrogenated to 2.4-dimethyl-4-tert-butyliceplane (II), bin 135-40°, at 1.4416, dx 0.7904. If was also prept as follows: 2.2.5-trimethyl-3-denamed (bx 57°, at 1.4370, dx 0.8463, prept. by hydrogenation of 2.2.3-trimethyl-5-hexand (bx 57°, at 1.4270, dx 0.8463, prept. by hydrogenation of 2.2.3-trimethyl-5-hexand (bx 57°, at 1.4524, dx 0.8455, which hydrogenated with I in the presence of Mg, as above, to 20% clefin, by 72-3°, at 1.4523, dx 0.8455, which hydrogenated to II, bix 129-30°, at 1.4523, dx 0.8455, which hydrogenated to II, bix 129-30°, at 1.4523, dx 0.8455, which hydrogenated with iodice gave 1.6-dimethyl-4-terpreptidenc-1.6-heptodices, by 42°, at 1.4637, dx 0.8569, which dehydrated with iodice gave 1.6-dimethyl-4-terpreptidenc-1.6-heptodices, by 42°, at 1.4768, dx 0.8153 (antidatimizate) heptodices, by 42°, at 1.4768, dx 0.8153 (antidatimizate)

Albert

VAYNSHTEYN, B.P.; KRUGLIKOV, V.Ya.; RAPOPORT, I.B.; VASIL'YEVA, Z.A.; KAGAN, L.Kh.; PLOKHINSKAYA, Ye.A.; VOLYNSKIY, A.V.; MIZOVSKIY, V.V.; KLEVTSOVA, V.P.; Prinimali uchastiye: MICHAN, A.I.; KONOVAL'CHIKOV, L.D.: AYNSHTEYN, V.G.; KVASHA, V.B.; CHELYANOVA, D.P.; ZAYTSEVA, A.F.; ANDREYEVA, T.A.

New way to synthesize oxygen compounds from carbon monoxide and hydrogen over iron-copper catalysts. Trudy VNII NP no. 9:177-196 '63. (MIRA 17:6)

KONOVAL®CHIKOV, O.D.; GALICH, P.N.; MUSIYENKO, V.P.; SKARCHENKO, V.K.; PETROV, A.A.

Effect of the porous structure of an alumina-chromium oxide catalyst on the conversion of n-hexane. Kin. i kat. 5 no.2: 350-354 Mr-Ap *64. (MIRA 17:8)

1. Institut khimii vysokomolekulyarnykh soyedineniy AN UkrSSR.

Dehydrogenation of n-hexane on activated carbon and Cr203-coal catalysts. Kin. i kat. 5 no.3:561-563 My-Je '64.

1. Institut khimii polimerov i monomerov AN UkrSSR.

IL'IN, N.A.; SURGETEVA, Ye.S.; KONOVAL'CHUK, M.Ya., tekhnik

System for a defectless production of goods. Tekst. prom. 25 no.5:4-6 My '65. (MIRA 18:5)

1. Direktor Bryanskogo kamvol'nogo kombinata (for Il'in). 2. Nachal'nik otdela truda i zarabotnoy platy Bryanskogo kamvol'nogo kombinata (for Sergeyeva).

KONOVALICHUK, M.Ya., takhnik

Technological study room as progress promoter. Tekst. prom. 25 no.10:81 0 65. (MERA 18:10)

l. Byuro tekhnicheskoy informatsii Bryanskogo kamvol*nogo kombinata.

SEREBRYAKOV, R.V.; DALIN, M.A.; KONOVAL'CHUKOV, A.C.

Some regularities in the reaction of cyanoethylation of hydrocyanic acid. Dokl. AN Azerb. SSR 19 no.11:31-34 '63. (MIRA 17:3)

1. BNIIolefin.

RPL WW/RM EWT(m)/EPF(e)/EPR/EWP(3)/T/EWA(c) Pc-4/Pr-4/Ps-4 L 52174-65

ACCESSION NR: AP5015484

UR/0286/65/000/008/0019/0019 547,239.2

AUTHOR: Serebryakov, B. R.; Konoval¹chukov, A. G.

TITLE: A method for producing succinic acid dinitrile. Class 12, No. 170050

SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 8, 1965, 19

TOPIC TAGS: succinic acid, amber, lignite, diacid, dinitrile

ARSTRACT: This Author's Certificate introduces a method for producing succinic But in initrile by cyanoethylation of hydrogen cyanide with acrylonitrile at 20-70°C in the presence of an alkali catalyst. The process is simplified by using ion-exchange resins which are insoluble in the reagent solution as the catalyst, e.g. EDE-10P anion exchanger in the sodium or potassium form.

ASSOCIATION: Vsesoyuznyy nauchno-issledovatel skiy tekhnologicheskiy institut po polucheniyu i perepabotke nizkomolekulyarnykn olefinov (All-Union Technological Scientific Research Institute for Producing and Processing Low-Molecular Olefins)

ENCL: 00

SUB CODE: MT, GC

SUBMITTED: 31Jul64


RG REF SOV:

OTHER: 000

MURASHKIN, 0., insh.; KONOVALENAK, A., inzh.

English language for ship engineers. Mor. flot 23 no.9:44
S '63.

(MIRA 16:11)



KONOVALENKO, A.F.

Some features of the installation of precast concrete sections of the No.3 shore pumping station. Energ. stroi. no.37: 58-60 '63. (MTRA 17:6)

l. Starshiy prizvoditel[†] rabot montazhnogo uchastka tresta "Yuzhenergomontazh."

RYVKIN, S.: KONOVALINIO B.

AENEVINEERIONS.

Photodiode from junction transistor. Radio no.2:41 F '58.
(Photoelectric cells) (MIRA 11:2)

obtained in this way should not be used under conditions of increased humidity.

1. Diodes--Design 2. Transistors--Applications

APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320015

Card 1/1

"APPROVED FOR RELEASE: 06/19/2000

CIA-RDP86-00513R000824320015-6

KoNOVAIENKO, B. M. USSR/Physics - Conductivity of Cds

FD-997

Card 1/1

: Pub. 153 - 1/24

Authors

: Ryvkin, S. M.; Konovalenko, B. M.; and Smetannikova, Yu. S.

Title

: Dependence of conductivity induced in layers and single-crystals of

cadmium sulfide upon energy of exciting electrons

Periodical

: Zhur. tekh fiz., 24, No. 6, 961-977, Jun 1954

Abstract

Present results of an investigation into the non-equilibrial (induced) conductivity in CdS layers that arises under the action of bombarding electrons with energies 2 to 30 kev. Show that, with decreasing energy of exciting electrons from 10 kev and lower, a sharp drop occurs in the "transverse" induced conductivity relative to unit energy incident on the specimen. This drop is explained by the decrease in depth of penetration of the electrons into the substance. An analogy exists between this drop in induced conductivity and the drop in photo-conductivity in the depth of the particular zone of light absorption. Acknowledge edvice of D. N. Nasledov. Twelve references: 7 USSR (L. G. Paritskiy, B. M. Angelov, S. V. Starodubtsev, V. P. Zhuze, V. A. Arkhangel'skaya,

A. M. Bonch-Bruyevich, S. M. Ryvkim).

Institution

rus er eneron . -

Submitted : Fo

: February 8, 1954

CIA-RDP86-00513R000824320015-6 "APPROVED FOR RELEASE: 06/19/2000

USSR/Physics - Photodiodes

FD-2398

Card 1/1

Pub. 153-2/21

Author

Alferov, Zh. I.; Konovalenko, B. M.; Ryvkin, S. M.; Tuchkevich, V. M.;

and Uvarov, A. I.

Title

Flat germanium photodiodes

Periodical:

Zhur. tekh. fiz. 25, 11-17, Jan 1955

Abstract

The authors describe the principal properties of germanium photodiodes of unique design and free from the usual deficiencies. In this design the illuminated area is not limited by the length of the diffusion displacement and can reach very large sizes corresponding to the total area of the n-p transition. They conclude: the germanium photodiode is a photocell valve to which considerable voltages can be applied in the closed direction; the sensitivity of the photodiode is about 300 times that of photocells with external photoeffect; the proper time of germanium photodiodes studied is about $1/10^{\frac{1}{2}}$ second, and can be decreased by decrease of the thickness of the n-germanium layer; the characteristics are very stable and free of "fatigue". Deficiencies are considerable temperature dependence of the dark current. The authors thank D. N. Nasledov, N. V. Shchetinina, and L. P. Bogomazov. Three references, including one USSR (S. M. Ryvkin, same issue, p. 21).

Institution:

Submitted:

October 13, 1954

USSR/Physics - Photodiodes

FD-2399

Card 1/1

Pub. 153-3/21

Author

Title

Konovalenko, B. M.; Ryvkin, S. M.; and Tuchkevich, V. M.

Sensitivity of germanium photodiodes to x-rays

Periodical:


Zhur. tekh. fiz. 25, 18-20, Jan 1955

Abstract : Numerous attempts have been made to utilize photocell valves as dosimeters of x-rays (e.g. V. M. Tuchkevich, Phys. ZS d. Sow. 5, 1934 and 7, 1935; I. M. Polyak and M. N. D'yachenko, ZhTF 22, 1952), but without practical results in consequence principally of the insufficient sensitivity. Recently a new type has been investigated, namely the germanium photodiode (same issue, p. 11; see preceding abstract). In the present article the authors expound certain results of their efforts on this problem; namely, they compare the sensitivity of germanium photodiodes and certain photocell valves under various conditions. They point to the possibility of the practical utilization of n-p transitions in germanium as dosimeters of intense x-rays (e.g. direct radiation). They thank D. Mc Masledov and N. I. Dodon. Six references: e.g. I. Shive, JOSA, 43, 1953; C. J. J. Millian, W. M., 10, 1970.

Institution:

Submitted :

October 13, 1954



- 1J. ++ r -. KONOVALENKO,

57-27-7-30/40

AUTHORS:

Ryvkin, S. M., Bogomazov, A. P.,

Konovalenko, B. M., Matveyev, O. A.

TITLE:

A Semiconductor Transmitter for Camma-Ray Indication (Poluprovodnikovyy datchik dlya indikatsii gamma-izlucheniya).

Zhurnal Tekhnicheskoy Fiziki, 1957, Vol. 27, Nr 7, PERIODICAL:

pp. 1601-1602 (USSR)

ABSTRACT:


As there exists a great want of cheap and simple devices, particularly of gamma-ray indicators, and as promising results were obtained in this respect with semiconductor-

materials, such as CdS and CdSe, whose conductivity substantially changes upon irradiation, the investigations

were here performed in this direction. In Zhurnal Tekhnicheskoy Fiziki, 1954, Vol. 24, p. 961 the authors showed that semicrystalline layers may form upon sublimation of CdS powder. The high temperature of the base, however, leads to the diffusion of the base-substance into the CdS-layer by which fact its properties with regard to sensitivity in the case of irradiation are greatly deteriorated. This difficulty was now overcome at the expense of a great increase in the speed of sublimation.

Card 1/2

CIA-RDP86-00513R000824320015-6" **APPROVED FOR RELEASE: 06/19/2000**



APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320015-6"

24-(6)-24,7700

Rywkin, S. M., Konovalenko, B. M.

66287 SOV/181-1-11-22/27

TITLE:

AUTHORS:

On the Dependence of Induced Conductivity of Cadmium Sulfide on the Energy of the Exciting Electrons

PERIODICAL:

Fizika tverdogo tela, 1959, Vol 1, Nr 11, pp 1757-1761 (USSR)

ABSTRACT:

According to reference 1 it was jointly established with Yu. S. Smetannikova that for 2 to 30 kev electrons with increasing electron energies, but with a total electron current intensity, which remains at the same level, the induced conductivity of the CdS reaches a saturation value, i.e. that this does not increase any more starting from a certain electron energy. The initial point of the "saturation" is not identical for different samples. Additional investigations (Ref 2) established that with small electron energies the decrease of the induced conductivity is related to the fact that the electrons do not deeply penetrate into the crystals and therefore the recombination processes occurring on the surface of the crystals have an increasingly important influence. Other authors (Ref 3) carried out similar investigations on "voluminous" monocrystals with 30 to 60 key-electrons. Their measuring results

Card 1/2

9.4300 (3203,1043,1143)

s/089/60/009/005/010/020 B006/B070

AUTHORS:

Konovalenko, B. M., Ryvkin, S. M., Yaroshetskiy, I. D.,

Bogomazov, L. P.

TITLE:


An Apparatus for Studying the Effect of Gamma Radiation


on Semiconductor Materials

PERIODICAL:

Atomnaya energiya, 1960, Vol. 9, No. 5, pp. 408 - 409

TEXT: In the present "Letter to the Editor", a cobalt apparatus for the study of the effect of gamma radiation on the electrical properties of semiconductors is described. The apparatus was developed in 1958 by, the Fiziko-tekhnicheskiy institut AN SSSR (Institute of Physics and Technology of the AS USSR). The principal use of the apparatus is in the production of defects that are constant in time. To obtain enough defects, fluxes of 10¹¹ cm⁻²sec⁻¹ are required. Fig.1 gives a schematic representation of the apparatus; Fig. 2 shows the experimental chamber. Both are described in detail. The dose rate was measured at different points of the chamber, and some of the results are given in a Table. The highest dose rate of 128 r/sec was found at the center of Card .1/3





"APPROVED FOR RELEASE: 06/19/2000

CIA-RDP86-00513R000824320015-6

314228 S/181/62/004/002/011/051 B102/B138

24,7700 (1035,1043,1385)

AUTHORS: Konovalenko, B. M., Ryvkin, S. M., and Yaroshetskiy, I. D.

TITLE: Radiation defects caused by fast electrons in n-type

germanium

PERIODICAL: Fizika tverdogo tela, v. 4, no. 2, 1962, 379-382

TEXT: The concentration M of radiation defects, the number 1 of the defect levels and their energies were determined for n-type Ge (\sim 1 ohm·cm, n \simeq 2·10¹⁵ cm⁻³) which was irradiated by 2.5-Mev electrons. The electron current density was \sim 5 μ a/cm², pulse duration was \sim 2 μ sec and repetition frequency was 50 sec⁻¹. The samples (8·1·1 mm³) were water-cooled. The electron energy behind the specimens was \sim 1.5 MeV, so that for calculations the electron energy in the specimen was taken to be \sim 2 MeV. Carrier concentration was determined by measuring the Hall constant between 77°K and room temperature. M and 1 were determined using the relations: n₂ = N_d - Ml₁ and n₄ = N_d - M(1-1); n₂ is the electron

Card (1/3)

3\L228 \$/181/62/004/002/011/051 B102/B138

Radiation defects caused by fast...

THE REPORT OF THE PERSON OF TH

concentration in the conduction band at low temperatures, when all defect levels are filled up and all donor levels are completely ionized (section I in Fig. 1). At high temperatures, when the upper defect levels are completely ionized, n₄ is the electron concentration (section II in . Fig. 1). M was also determined from the activation energy of the upper levels and the carrier concentration of the linear part of II, using the relation $n-n_2 = \sqrt{MN_c} \exp(-\Delta E_M/2kT)$. N_c was calculated for the effective mass $m_n^* = 0.25 m_0$. For several different specimens, the following results were obtained: N_d was $(2.08 - 2.26) \cdot 10^{15}$ cm⁻³, Ml was $(1.65 - 2.03) \cdot 10^{15}$ cm⁻³, M was $(4.25 - 5.2) \cdot 10^{14}$ cm⁻³, 1 was 3.9 - 4.2, ΔE_{M} 0.20 - 0.23 ev, and the radiation defect formation cross section was 1.45-1.55 barn; it was calculated from $\sigma = M/\delta N_{Ge}$, δ - electron flux density, N_{Ge} - number of Ge atoms per cm3. Electrons with ~25 Mev were found to produce defects with the following levels: E_c -0.24 ev, E_c -0.36 ev, E_v +0.25 ev and E_v +0.11 ev, There are 3 figures, 2 tables, and 7 references: 3 Soviet and 4 non-Soviet. The three references to English-language publications read as Card 2/3

3/1228 \$/161/62/004/002/011/051 B102/5138

Radiation defects caused by fact...

follows: J. U. Cleland et al. Phys. Rev. <u>102</u>, 772, 1956; W. L. Brown et al. Phys. Rev. <u>92</u>, 591, 1953; J. J. Cleland, L. J. H. Crawford. Progress in Semiconductors, <u>2</u>, 1957.

ASSOCIATION: Fiziko-tekhnicheskiy institut im. A. F. Ioffe AN SSSR

Leningrad (Physicotecnnical Institute imeni A. F. Ioffe

AS USSR, Leningrad)

SUBMITTED: August 8, 1961

19 n 15.1 15.0 14.9 14.8 2 3 4 5 5 7 8 7.8

Fig. 1

Card 3/3

RYVKIN, S.M.; DOBREGO, V.P.; KONOVALENKO, B.M.; YAROSHETSKIY, I.D.

Induced impurity breakdown in compensated germanium and courrent oscillations related to it. Fiz.tver.tela & no.7;
1911-1914 J1 '62. (MIRA 16:6)

1. Fiziko-tekhnicheskiy institut imeni A.F. Ioffe AN SSSR,
(Breakdown, Electric) (Germanium—Electric properties)

The second secon	ACCESSICN MR: AP3CO3878 AUTHOR: Vitovskiy, N. A.; Konovslenko, B. M.; Mashoveta, T. V.; Rykvkin, S. M.; TITLE: Gamma-ray-generated defects in germanium 1 SOURCE: Exactly	
	TOPIC TAGS: gamma-ray semiconductor irradiation, radiation defect, monopolar annealing, bipolar annealing, germanium irradiation, germanium defect, monopolar ABSTRACT: In the latest stage of research on the subject, define her was doned and an anneal p-type specimen on the subject, define her	
	between 1012 to 1015 cm ⁻¹ . The source was Co50 at a dosage of 2.10 ¹² to 8.10 ¹⁵ and temperature of 100. The work was aimed at clarifying the saturation of radiated specimens which occurs after polarity reversal, whereby first	
,	energy. While the saturation process is evident up to very high concentrations	

KONOVALENKO, B.M.; RYVKIN, S.M.; YAROSHETSKIY, I.D.

Radiation defects in germanium caused by fast 28 Mev. electrons. Fiz. tver. tela 5 no.8:2075-2086 Ag '63. (MIRA 16:9)

1. Fiziko-tekhnicheskiy institut im. A.F. Ioffe AN SSSR, Leningrad. (Germanium crystals-Defects) (Electrons)

"APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320015-6 L 12006-65 ENT(1)/ENG(k)/ENT(m)/EPF(c)/EPF(n)-2/EEC(t)/EMP(b)/EMP(t) Pr-4/Pu-4 IJP(c)/AS(mp)-2/AFWL/SSD/ASD(a)-5/BSD/ESD(gs) ESD(t) ACCESSION NR: AP4046643 JD/GG/AT S/0181/64/006/010/3166/3168 B AUTHOR: Gerasimov, A. B.; Konovalenko, B. M.; Yaroshetskiy, I. D.; Barkalaya, A. A. TITLE: Impurity photoconductivity produced in germanium by gammaray irradiation SOURCE: Fizika tverdogo tela, v. 6, no. 10, 1964, 3166-3168 TOPIC TAGS: gamma irradiation, photoconductivity, germanium, forbidden band, line spectrum, carrier density, impurity conductivity ABSTRACT: This is a continuation of earlier research in which one of the authors participated (s. M. Ry*vkin, R. Yu. Khansevarov, I. D. Yaroshetskiy, FTT v. 3, 211, 1961), using a larger γ -ray flux in order to observe a more extensive line spectrum in the forbidden band In this case n- and p-type germanium with initial carrier densities n = $(2--6) \times 10^{13}$ and $p_{\theta} = (0.6--2) \times 10^{13}$ cm⁻³ were used. The samples

L 12006-65

ACCESSION NR: AP4046643

were exposed to γ rays from Co^{60} at a dose rate 80--90 r/sec, using an installation described elsewhere (B. M. Konovalenko, S. M. Ry*vkin, I. D. Yaroshetskiy, and L. P. Bogomazov, Atomnaya energiya v. 9, 408, 1960). The results are illustrated in Fig. 1 of the enclosure. The spectral curves disclose a large number of bends and ledges, pointing to a complicated spectrum of the local levels in the forbidden band. Measurements of all the investigated samples indicate the presence of the following energy levels: E_V + 0.52, $E_v + 0.48$, $E_v + 0.43$, $E_v + 0.41$, $E_v + 0.37$, $E_v + 0.33$, $E_v + 0.31$, and E, + 0.27. This spectrum coincides fully with the spectrum of the local levels produced in the central part of the forbidden band when germanium is irradiated with fast neutrons, to which the levels with energies $E_{\rm V}$ + 0.31 and $E_{\rm V}$ + 0.43 eV, which are symmetrical relative to the center of the forbidden band, are added. It is further concluded that the various levels introduced by impurities in the central part of the forbidden band are not due to any clustering of the point defects with the atoms of the doping impur-

L 12006-65

ACCESSION NR: AP4046643

ity. "The authors are deeply grateful to S. M. Ry*vkin for a discussion of the results." Orig. art. has: 1 figure.

ASSOCIATION: Fiziko~tekhnicheskiy institut im. A. F. Ioffe AN SSSR

SUBMITTED: 18May64

ATD PRESS: 3120

ENCL: 01

SUB CODE: IC, NP

NO REF SOV: 003

OTHER: 000

Card 3/4

L 12027-65 EWT(1)/EWG(k)/EWT(m)/EPA(sp)-2/EPA(w)-2/EEG(t)/EWP(t)/ERG(b)-2/EWP(b)/EMA(n)-2 Pz-6/Pab-10/Peb IJP(c)/SSD/ESD/AS(mp)-2/ASD(n)-3/AFWL/

ACCESSION NR: AP4046651

\$/0181/64/006/010/3184/3186

AUTHOR: Gerasimov, A. B.; Konovalenko, B. M.

TITLE: Low-temperature irradiation of germanium with fast electrons

SOURCE: Fizika tverdogo tela. v. 6, no. 10, 1964, 31/34-3186

TOPIC TAGS: germanium, electron irradiation, low temperature research, dislocation effect, annealing, impurity conductivity, photoconductivity

ABSTRACT: Preliminary results are presented on low-temperature irradiation of n-type Ge with $N_{\rm d}=2\times10^{14}-2\times10^{15}~{\rm cm}^{-3}$, including samples without and with dislocations (dislocation density $10^7-10^8~{\rm cm}^{-2}$), and also of p-type Ge with $N_{\rm d}=8\times10^{14}-4\times10^{15}~{\rm cm}^{-3}$. The samples were irradiated with 3.5-MeV electrons at T = 77K (the samples were kept in liquid nitrogen). The irradiated samples were kept in the nitrogen for several days until their resistance sta-

Card 1/5

L 12027-65 ACCESSION NR: AP4046651

bilized, and then subjected to isochronous annealing to room temperature with an interval of 20-30° between annealing points and with an annealing time 15 minutes. After each annealing, measurements were made at 77K of the Hall coefficient, the conductivity, and of the spectral characteristic of the impurity photoconductivity. All ntype samples were converted by irradiation with doses of 2.7 x 1016 and 1.1 x 10^{17} el/cm² into p-type with a Fermi level located near μ = = E_v + 0.1 ev. A typical plot of the variation of the conductivity during the annealing is shown in Fig. 1 of the enclosure. The impurity photoconductivity spectral characteristic was strongly dependent on the annealing stage, as illustrated in Fig. 2 of the enclosure. The measurements on n-type samples showed that the low-temperature irradiation produces, other conditions being equal, entirely different results than irradiation at room temperature. This difference is manifest in the fact that at low temperatures the Fermi level drops much lower. A noticeable difference in the Fermi level is observed also when a comparison is made between the results

Card 2/5

L 12027-65

ACCESSION NR: AP4046651

of low-temperature irradiation and irradiation at room temperature of samples with and without dislocations. All the results indicate that stepwise isochronous annealing brings about noticeable changes in the structure of the radiation defects produced by low-temperature irradiation of germanium. "The authors are grateful to S. M. Ry*vkin and I. D. Yaroshetskiy for a discussion of the work, and to V. A. Petrovskiy for collaborating with the irradiation of the samples." Orig. art. has: 2 figures.

ASSOCIATION: Fiziko-tekhnicheskiy institut im. A. F. Ioffe AN SSSR (Physicotechnical Institute, AN SSSR)

SUBMITTED: 01Jun64 ATD PRESS:


3120

ENC1 02

SUB CODE: IC, NP

NO REF SOV: 005

OTHER: 002



ENT(1)/ENT(m)/EPA(w)-2/T/ENP(t)/ENP(b)/ENA(m)-2 UR/0181/65/007/008/2545/2547 ACCESSION NR: AP5019886 AUTHOR: Gerasimov, A. B.; Konovalenko, B. M. TITLE: Low-temperature annealing of germanium irradiated with fast electrons SOURCE: Fizika tverdogo tela, v. 7, no. 8, 1965, 2545-2547 TOPIC TAGS: annealing, metal heat treatment, electron beam hardening ARSTRACT: Results are presented of an investigation of isochronous annealing of called the discensivith different donor concentrations, incalled the with comparatively small, Thomas of 3-Bev electrons (fluxes insufficient to change the type of conduc-. Three annealing stages appeared clearly: at 120-140K, 190-220K, and 2/0-300K. In each or these stages the carries on atrations changed monotonically in the disease ref the initial value (before once ration). The temperature range of each stage is predically the same as recens which changed their conductivity to betyee. In most of the n- and - 1. Thems (after irradiation) the mobility of the country of the second year recent a maximum. With a further rise of temperature, additing decreased in the n-type specimens, while in the p-type specimens it remained practically constant. Activation energies for all three stages were determined for n- and p-type isotherm-**Card** 1/2

L 61896-65

ACCESSION NR: AP5019886

 \mathcal{Q}

ally annealed specimens. The following values were obtained:

 $E_1 = (0.27 \pm 0.03)$ ev, $E_2 = (0.66 \pm 0.05)$ ev, and $E_3 = (1.08 \pm 0.1)$ ev.

The activation energies for the second and third stages were close to the activation energy values for the migration of vacancies and interstitial atoms in germanium (1.76 and 0.6 ev); the second stage apparently is associated with the migration of interstitial atoms, while the third stage is related to the migration of vacancies.

The first stage, it is possible that recombination of rearry Frenkel defects takes place. In the first stage the Fermi level shifted toward the ion band, while the spectral distribution of photoconductivity in specimens which changed their type of conductivity did not change. For the second stage an increase in carrier concentrations in specimens of both types was characteristic. During the third stage the Fermi level rose in all specimens. Orig. art. has: 1 figure.

(JA)

ASSOCIATION: Fiziko-tekhnicheskiy institut im. A. F. Ioffe AN SSSR, Leningrad Physioptechnical Institute, AN SSSR); Tbilisskiy gosudarstvornyy universitet (Tbilisi State University)

SUBMITTED: 25Mar65 NO REF SQV: 001 ENCL: 00 OTHER: 003 SUB CODE: MM,NP ATD PRESS: 4060

Card 2/21m


APPROVED FOR RELEASE: 06/19/2000 CIA-RDF

CIA-RDP86-00513R000824320015-6"

L 65058-65 EWT(1)/EWT(m)/EPF(c)/EPF(n)-2/T/	YEWA(h) IJP(c) GG/	AT
AUTHOR: Gerasimov, A. B.; Dolidze, N. D.; Ko	UR/0181/65/00 ₩4,45	07/008/2562/2 563
AUTHOR: Gerasimov, A. B.; Dolidze, N. D.; Ko	novalenko, B. M.; Ryv	dn, S. M. 4 ^d , 5
FITLE: On the character of the hysteresis of germanium n-p junction produced by irradiation of the counce of the hysteresis of germanium n-p junction produced by irradiation of the hysteresis of germanium n-p junction produced by irradiation of the hysteresis of the hysteresis of the hysteresis of the hysteresis of germanium n-p junction produced by irradiation of the hysteresis of the h	f the volt-ampere char	acteristic of a 7-9 43
POPIC TAGS: germanium, volt ampere character tric hysteresis, semiconductor research	ristic, electron bombe	rdment, elec
ABSTRACT: The authors observed a hysteresis junction produced by bombarding n-Ge single continuous contracteristic obtained at 77K who carrier direction is shown in Fig. 1 of the Ethe fact that when the voltage is increased to	erystals with fast elementhe sample was illustrated inclosure. The hyster the characteristic is re-	etrons. The luminated in the esis consists in epresented by
the lower carve, when the voltage reaches V ₁ and when the voltage is then decreased the ch		sented by the 🛒 🛊
		ie breakdowii :
upper curve. If the barrier-layer voltage is occurs at voltages lower than V ₁ . This hyste the sample consists of two series-connected p down takes place and whose volt-ampere charac	s applied in pulses, the resis can be explained earts, an element in wh	l by assuming that nich the break-

L 65058-65 AP5019894 ACCESSION NR: portion, and one which exhibits ballast properties. The former is identified with the n-p junction itself, and the latter with the high-resistance portion of the sample. The effect of deep levels on the breakdown characteristics is discussed briefly from the point of view of space charge exchange inside the sample. Orig. [02] art. has: 2 figures. ASSOCIATION: Fiziko-tekhnicheskiy institut im. A. F. Ioffe AN SSSR, Leningrad (Physicotechnical Institute, AN SSSR); Tbilisskiy gosudarstvennyy universitet Toilisi State University) SUB CODE: 01 ENCL: SUBMITTED: 07Apr65 ATD PRESS: 4084 OTHER: 002 NO REF SOV: 005 Card 2/3

"APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320015-6



APPROVED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320015-6"

I. 00899-67 ENT(1)/ENT(m)/ENP(t)/ETI IJP(c) AT/JD
ACC NO. AP6033561 SOURCE CODE: UR/0181/66/008/010/2994/2998

AUTHOR: Gerasimov, A. B.; Konovalenko, B. M.; Kotina, I. M.; Umarova, Kh. F.

ORG: Physicotechnical Institute imeni A. F. Ioffe AN SSSR, Leningrad (Fizikotekinicheskiy institut) AN SSSR

TITLE: Kinetics of bipolar impurity photoconductivity of silicon with radiation defects

SOURCE: Fizika tverdogo tela, v. 8, no. 10, 1966, 2994-2998

TOPIC TAGS: photoconductivity, bipolar photoconductivity, radiation, radiation defect, conductivity

ABSTRACT: Silicon samples with radiation defects at T = 77K were observed to be characterized by distinctive kinetics in the increase of their impurity photoconductivity. An explanation is offered for this phenomenon, which is shown to be related to the bipolarity of impurity excitation, and an approximate computation is made of the kinetics of inverse overcharge for a case of low level excitation. The

Card 1/2

C NR: AP603	3561				0		
cross-section of hole capture at the radiation defect level E _c -0. 40 ev is determined. Orig. art. has: 7 formulas and 5 figures. [Authors' abstract]							
SUB CODE: 2	0/ SUBM DATE:	28Mar66/	ORIG REF: 004/	OTH REF:	002/		
			·				
	•						
;							
	·						
	•						
rd 2/2m/s_	•						

ACC NR: AP6036962

(A,N)

SOURCE CODE: UR/0181/66/008/011/3226/3231

AUTHOR: Gerasimov, A. B.; Konovalenko, B. M.; Ryvkin, S. M.; Umarova, Kh. F.; Yaroshetskiy, I. D.

ORG: Physicotechnical Institute im. A. F. Toffe, AN SSSR, Leningrad (Fiziko-tekhni-cheskiy institut AN SSSR)

TITIE: Photoelectret state in silicon with radiation defects

SOURCE: Fizika tverdogo tela, v. 8, no. 11, 1966, 3226-3231

TOPIC TAGS: photoelectret, crystalline silicon, radiation effect

ABSTRACT: The photoelectret state (PS) and the dependence of its properties on the concentration of free carriers and the concentration of locallevels in the forbidden band were studied on two groups of n- and p-type silicon samples with different positions of the Fermi level after irradiation with fast electrons (which produced radiation defects). The dependence of dark polarization on the time of application of the polarizing voltage and its magnitude was measured, this being one of the chief characteristics of PS. Differences in the PS of the two groups of samples were also manifested in the persistence of polarization. The spectral selectivity of the PS was also determined. Analysis of the spectral curves showed characteristics corresponding to certain local levels of radiation defects; the curves break off abruptly in the shortwave range on passing to bipolar excitation, starting at quantum energies at

Card 1/2

ACC NR. AR PROMED FOR RELEASE: 06/19/2000 CIA-RDP86-00513R000824320015-6

which the formation of minority carriers is possible: The results of the study of PS during bipolar excitation are interpreted in the light of the substantial role played by optical charge exchange between impurity centers in the observed effect. Authors take this opportunity to thank I. M. Kotina for her assistance. Orig. art. has: 7

SUB CODE: 20/ SUBM DATE: 07Apr66/ ORIG REF: 009/ OTH REF: 001